

GEOLOGY

Limestone

BEST USE

Exterior Walls of Buildings and Fireplaces Stone Shall be Mortared In

WEIGHT CALCULATOR PER SQUARE FOOT OF FLATS AND LINEAL FOOT OF CORNERS

14.9 Lbs Average Per Sf

19.1 Lbs Average Per Lf

QUANTITY PER PALLET/CRATE

Full Bed Veneer: 4,000 Lbs

Thin Veneer: 150 Sf (2,200-2,300 Lbs)
200 (3,000-3,100)



CELESTE *Rubble*

FULL VENEER

Common Coverage

Standard Joint

40 Square Feet / Ton

Dry Stack

30 Sf / Ton

Overgrout

50 Sf / Ton

DIMENSIONS

Random Sizes:

3"-10"

Thickness:

3"-5"

TYPICAL CHARACTERISTICS

Chopped All Sides

Random Rectangular Shapes

STANDARD SIZE TOLERANCE

Thickness:

3"- 5.5"

SHIPPING DETAILS: FULL TRUCK QUANTITY

Flatbed: 12-13 Pallets

Dry Van: 12-13 Pallets

Rail Container: 12-13 Pallets

THIN VENEER

Common Coverage

Standard Joint

200 Square Feet

Per Crate

Dry Stack

180 Sf / Ton

Overgrout

220 Sf / Ton

DIMENSIONS

Random Sizes:

3"-10"

Thickness:

1"-1.5"

Corner Returns:

3"-5"

TYPICAL PIECE

Chopped All Sides

Random Rectangular Shapes

STANDARD SIZE TOLERANCE

Thickness:

1"-1.5"

SHIPPING DETAILS: FULL TRUCK QUANTITY

Flatbed: 21-22 Pallets / 17-18 Crates

Dry Van: 19-20 Pallets / 15-16 Crates

Rail Container: 18-19 Pallets / 14-15 Crates

ASTM TESTING

Compressive Strength (psi).....11,580

Flexural Strength (g)..... 1,170

Freeze/Thaw Loss (%)..... 0.08

Average 48-hr Absorption (%)..... 0.63