

**GEOLOGY**

Limestone

**BEST USE**

Exterior Walls of Buildings and Fireplace Stone Shall be Mortared In

**WEIGHT CALCULATOR PER SQUARE FOOT OF FLATS AND LINEAL FOOT OF CORNERS**

13 Lbs Average Per Sf

17 Lbs Average Per Lf

**QUANTITY PER PALLET/CRATE**

Full Bed Veneer: 4000 Lbs (80-90 SF)

Thin Veneer: 200SF (2100-2300)



**TEXAS SHELL *Traditional***

**FULL VENEER**

Common Coverage

<b>Standard joint</b>	<b>Dry Stack</b>	<b>Overgrout</b>
40 square feet / ton	30 Sf / ton	50 Sf / ton

**DIMENSIONS**

- 2" high X 8"-18" lengths
- 4" high X 8"-18" lengths
- 6" high X 8"-18" lengths
- 8" high X 8"-18" lengths
- 10" high X 8"-18" lengths
- 12" high X 8"-18" lengths
- Thickness: 3"-5"

**TYPICAL PIECE**

Sawn Top and Bottom w/ Snapped Ends  
Rectilinear Shape

**STANDARD SIZE TOLERANCE**

Height:	1/8" +/- Less
Thickness:	3"-5.5"

**SHIPPING DETAILS: FULL TRUCK QUANTITY**

Flatbed:	12-13 Pallets
Dry Van:	12-13 Pallets
Rail Container:	12-13 Pallets

**THIN VENEER**

Common Coverage

<b>Standard joint</b>	per crate	<b>Overgrout</b>
200 square feet	<b>Dry Stack</b>	220 Sf /ton
	180 Sf / ton	

**DIMENSIONS**

- 2" high X 8"-18" lengths
- 4" high X 8"-18" lengths
- 6" high X 8"-18" lengths
- 8" high X 8"-18" lengths
- 10" high X 8"-18" lengths
- 12" high X 8"-18" lengths
- Thickness: 1"-1.5"
- Corner Returns: 3"-5"

**TYPICAL PIECE**

Sawn Top and Bottom w/ Snapped Ends  
Rectilinear Shape

**STANDARD SIZE TOLERANCE**

Height:	1/8" +/- Less
Thickness:	1"-1.5"

**SHIPPING DETAILS: FULL TRUCK QUANTITY**

Flatbed:	21-22 Pallets / 17-18 Crates
Dryvan:	19-20 Pallets / 15-16 Crates
Rail Container:	18-19 Pallets / 14-15 Crates

**ASTM TESTING**

Average 48-hr Absorption (%).....	8.55
Average Bulk Specific Gravity .....	1.92
Average Modulus of Rupture (psi) .....	542
Average Compressive Strength - Perpendicular (psi) .....	1,630
Average Compressive Strength - Parallel (psi) .....	1,994