

GEOLOGY

Limestone

BEST USE

Exterior Walls of Buildings and Fireplaces Stone Shall be Mortared In

WEIGHT CALCULATOR PER SQUARE FOOT OF FLATS AND LINEAL FOOT OF CORNERS


14.9 Lbs Average Per Sf

19.1 Lbs Average Per Lf

QUANTITY PER PALLET/CRATE

Full Bed Veneer: 3,800 Lbs

Thin Veneer: 165 SF (1,900-2,000 Lbs)



AYA MOSAIC

FULL VENEER

Common Coverage

Standard Joint	Dry Stack	Overgrout
40 Square Feet / Ton	30 Sf / Ton	50 Sf / Ton

DIMENSIONS

Random Sizes:	3"-12"
Thickness:	3"-5"

TYPICAL CHARACTERISTICS

Natural face, chopped all sides
Irregular shapes with 3-5 points

STANDARD SIZE TOLERANCE

Thickness:	3"-5.5"
------------	---------

SHIPPING DETAILS: FULL TRUCK QUANTITY

Flatbed:	12-13 Pallets
Dry Van:	12-13 Pallets
Rail Container:	12-13 Pallets

THIN VENEER

Common Coverage

Standard Joint	Per Crate Dry Stack	Overgrout
165 Square Feet	180 Sf / Ton	220 Sf / Ton

DIMENSIONS

Random Sizes:	3"-12"
Thickness:	1"-1.5"
Corner Returns:	3"-5"

TYPICAL PIECE

Natural face, chopped all sides
Irregular shapes with 3-5 points

STANDARD SIZE TOLERANCE

Thickness:	1"-1.5"
------------	---------

SHIPPING DETAILS: FULL TRUCK QUANTITY

Flatbed:	18-20 Pallets / 18-20 Crates
Dry Van:	18-20 Pallets / 18-20 Crates
Rail Container:	18 Pallets / 18 Crates

ASTM TESTING

Compressive Strength (psi)	12,520
Flexural Strength (g)	2,330
Freeze/Thaw Loss (%)	0.00
Average 48-hr Absorption (%)	1.8